



Model 85801

Dispense Pak #1 Model 85801

For 5-gallon pail, single-gun applications not exceeding 26 cu. in. (426 cc) per minute.

Air Inlet	Material Outlet	Control Valve Inlet	Control Valve Outlet
¼" NPTF	½" NPTF	¼" NPTF	⅛" NPTF ¹

Diameter in. / mm	cu. in. / cc	Gallons / Liters	Ft. per Gal.
⅛" / 3.2	.1473 / 2.41	.00064 / .0024	1565
¼" / 6.35	.5891 / 9.65	.00255 / .0096	392
⅜" / 9.525	1.3562 / 22.2	.00574 / .021	174
½" / 12.7	2.3562 / 38.6	.01020 / .038	98
⅝" / 15.875	3.8612 / 63.3	.01592 / .060	63
¾" / 19.05	5.3005 / 86.8	.02295 / .086	44

85801 consists of 1725 pump assy., 67176 coupling, 83586 flow gun, 83594 universal swivel, 85817 20' x ½" ID moisture-lok hose assy.

¹ For additional nozzle selections refer to page 22.



Model 1725

Model 1725

Portable package designed for original 5-gallon pails. Portable pressure primer includes reversible steel cleats for securing both straight-sided and tapered pails. Follower with wiper blade cleans sides of pail as material is dispensed. Air-assisted follower extraction.

Model No.	Pump Ratio	Drum Size	Max. Del. gal./min. l./min.	Max. Discharge Pressure psi / bar	Hose Description	Standard Accessories
1725	25:1	5 gal.	0.25 / 0.95	5000 / 340	NA	NA

Note: Order hose, flow gun, etc. separately.



Model 252

Model 252

For dispensing heavy greases, NLGI #3. Includes a screw prime follower.

Note: Model includes 7 ft. of ¼" high-pressure hose, 81387 universal swivel and 740 control valve. Pressure switch is factory set to shut-off pump at 5,000 psi lubricant pressure and to start pump when pressure drops to 2,500 psi.

Dimensions	Output	Power Requirements	Lubricant Capacity
36¼" x 28" x 17½" 921 x 711 x 445 mm	6 oz. / min. 177.6 cc / min	115/230 volt 5.4 / 2.7 amp	30 lbs. 13.6 kg.