



Model 87212

Model:	87212		
Type:	Hydraulic		
Ratio:	5:1		
Hydraulic Pressure:	Min.	200 psi	14 bar
	Max.	1000 psi	68 bar
Lubricant Output/Cycle:	Min.	.010 cu. in.	.164 cc
	Max.	.060 cu. in.	.983 cc
Cylinder Type:	Double acting		
Directional Valve Requirements:	4-Way		

Model 87214

Model:	87214		
Type:	Air		
Ratio:	18:1		
Air Pressure:	Min.	60 psi	4 bar
	Max.	200 psi	14 bar
Lubricant Output/Cycle:	Min.	.010 cu. in.	.164 cc
	Max.	.060 cu. in.	.983 cc
Cylinder Type:	Single acting		
Directional Valve Requirements:	3-Way		

Note:
Pumps include Buna-N O-rings.

Modular LP-Style Reservoirs

Mount directly to LP pumps. Includes 3000 psig (200 bar) gauge and 900 psig (60 bar) atmospheric indicator. Transparent, polycarbonate construction.



Model	Lubricant Type	Capacity					Air Hydraulic	Lube Outlet	Dimensions - in. / mm		
		lb/pint	kg	liter	cu. in.	cc			Height	Width	Depth
87402	Grease	3 lb	1.36	—	90	1475	1/8"	1/8"	11.625	6.78	7.06
87403		5 lb	2.27	—	150	2450			295.3		
87405	Oil	5 pint	—	2.36	144	2365	NPSM(F)	NPSM(F)	14.625 371.5	172.2	179.6