



Cycle Switch

Cycle Switch attaches to valve with cycle indicator pin, sends electrical signal to controller.

Model	Switch Type	Switch Capacity	Conduit Connector
87070	SPDT	15 Amps @ 125/250 VAC 0.5 Amps @ 125 VDC	½" - 14 NPSM



Cycle Counter

Cycle Counter attaches to valve with cycle indicator pin, counts and records cycles.

Model	Maximum Counts
87828	99,999



Proximity Switch

Proximity Switch is a magnetic reed switch that attaches to divider valve for use in hazardous environments.

Model	Block Style	Switch Type	Switch Capacity	CSA Certification	Conduit Connector
85651	UV	SPST	10 Watts 200 VDC 0.5 Amp	Class I, Group A, B, C & D Class II, Group E, F & G Hazardous Locations	½" NPT(F)
87617	MC				
87618	XL Size 03 thru 12				



External Singling/Cross Port Kit

External Cross Port Kit connects alternate outlet ports to combine the volume of two divider valves through a single outlet.

Model	Block Type	Application/Usage
87905	MC	Single and Crossport
87823	XL	Crossport
87824	XL	Singling
87825	UV	Crossport



Balancing Valve

Model 87865 Balancing Valve is used when back pressure differential between divider valve outlets exceeds 1000 psi (68 bar).

Model	Pressure Adjustment				Inlet/ Outlet	Seal Material
	Min		Max			
	psig	bar	psig	bar		
87865	250	17	6000	408	½" NPTF(F)	Viton®




Mounting Bracket

Model 250286 (UV) and Model 360675 (MC) Mounting Brackets—
Mount divider valve assembly off the face of vertical surfaces. Use two brackets per divider valve assembly.


Check Valves

Check valves maintain prime in feed lines and check back pressure from pressurized lubrication points.




Double Ball, Straight

Model	Pressure		Inlet	Outlet	Hex Material	Hex Inlet-in.	Hex Outlet-in.	Length in./mm
	Max	Opening						
880511	8000 psig	145 psig	1/4"	1/4"	Carbon Steel	13/16"	3/4"	3.72/94.5
880518-9			NPTF(F)	NPTF(M)	316 S.S.			3.75/95.3
880517	550 bar	10 bar	1/8"	1/8"	Carbon Steel			3.31
880519-9			NPTF(F)	NPTF(M)	316 S.S.			
880015-9	5000 psig 340 bar	80 psig 6 bar	9/16-18 UNF	7/16-20 UNF	Stainless Steel	3/4"	2.75/70	




Ball & Poppet, Straight

Model	Pressure		Inlet	Outlet	Hex Material	Hex Inlet-in.	Hex Outlet-in.	Length in. / mm
	Max	Opening						
880513	2000 psig	50 psig	1/8" NPTF(F)	1/8" NPTF(M)	Carbon Steel	3/4"	13/16"	2.75 70.0
880514	140 bar	3.5 bar	1/4" NPTF(F)	1/4" NPTF(M)				3.06 77.7



Ball Type, Straight

Model	Pressure		Inlet	Outlet	Hex Material	Hex in.	Length in. / mm
	Max	Opening					
87817	7500 psig	20-70 psig	1/4" NPTF(M)	1/4" NPSF(F)	Carbon Steel	11/16"	1.38/35.1
87818	500 bar	1.5-5 bar	1/8" NPTF(M)	1/8" NPTF(F)		9/16"	1.19/30.2
130021-3	6000 psig 400 bar	31-70 psig 2-5 bar	1/8" NPTF(F)	1/8" NPTF(M)		1/2"	1.06/27.0



Ball & Poppet, 90°

Model	Pressure		Inlet	Outlet	Hex Material	Hex Inlet in.	Hex Outlet in.	Dimensions in. / mm	
	Max	Opening						A	B
880515	2000psig 140 bar	50 psig 3.5 bar	1/8" NPTF(F)	1/8" NPTF(M)	Carbon Steel	3/4"	13/16"	3.38 86	1.25 31.8