



Modular Pump Baseplates

Mount pump directly to a modular reservoir with intermediate baseplate.
Use machine mounted baseplates with remote reservoirs.

Model	Description	Use with Pump Model	Air/ Hydraulic Inlet	Lube Inlet	Lube Outlet	Dimensions in. / mm			Atmos. Indicator psi / bar
						Height	Width	Depth	
87218	Inter-mediate	87200, 87202, 87216	1/8" NPTF(F)	—	1/4" NPTF(F)	3.25	3.25	1.00	1450 100
87204	Machine Mount					82.6	82.6		
130095		130179	1/4" NPTF(F)	3/8" NPTF(F)		4.00	4.50	150	

Note:

Baseplates include flouroelastomer O-rings for standard or synthetic lubricants.



Modular Reservoirs for Oil Systems

Model	Type		Capacity				Material	Dimensions - in. / mm			
	Style	Outlet	gal.	liter	cu. in.	cc		Height	Width	Depth	
87400	Cylindrical	1/2" NPTF(F)	.625	2.4	144	2350	Acrylic	15.69	6.00	5.31	
87413			1.25	4.7	289	4750		17.69	7.31	7.47	
87417	Tank	3/8" NPTF(F)	5	18.9	1155	18900	Steel	10.12 257.4	17.50	12.56	
87418			3	11.3	693	11350			445.2	13.50	11.56
87419			1.5	5.7	346	5675			267.1	10.50	7.56
								186.0	192.3		

Note:

All reservoirs will accept 87218 Intermediate Baseplates.

Modular Reservoirs for Grease Systems



Model	Capacity				Material	Dimensions - in. / mm		
	lbs.	kg	cu. in.	cc		Height	Width	Depth
87406	10	4.54	300	4900	Acrylic	17.69	7.31	7.47
87416	15	6.82	450	7350		450		186.0
87421 *	10	4.54	300	4900	Steel	25.19	7.31	7.47
87423 *	15	6.82	450	7350		640.8		186.0
						17.69	7.31	7.41
						450		186.0
						25.19		
						640.8		

* Includes visual level indicator rod.

Note:

All reservoirs accept Model 87218 Intermediate Baseplates. Reservoirs include standard 1/2" NPTF(F) outlet. Filler fitting Model 632004.