

# LINCOLN



## **LINCOLN'S MODEL 3624 USED FLUID TANK**

- High-strength polyethylene reinforced tank and bowl means no corrosion, no denting, no swelling
- Evacuates easily with standard shop air
- Large capacity: 26 gallon / 100 liter
- Large tool tray and convenient oil filter drain are built into the top of the tank
- Includes fluid level sight gauge, fixed air regulator and safety relief valve
- Professional look and outstanding shop features together in one assembly
- Compatible with virtually all used fluids (motor oil, transmission fluid, power steering fluid, and engine coolant)



**PRESSURIZED EVACUATION  
IN A MOBILE, SHOP-FRIENDLY DESIGN**

# Loaded with features, the Model 3624 is a great addition to any shop or maintenance facility

## Pressurized

Lincoln's model 3624 unique pressurized tank quickly evacuates fluid in just three minutes.\*

## Durable

Unlike metal tanks, the reinforced high-strength polyethylene will not dent or scratch. The 3624 will maintain its appearance for years and will not swell under pressure.

## Safe

The tank's polyethylene material greatly reduces risk to surrounding vehicles. The pressure relief valve and fixed air regulator ensure a safe work environment.

## Convenient

The fluid level sight gauge, large tool tray and oil filter drain help optimized labor time and cleanliness.

\* At 72°F

## Model 3624 Specifications

Capacity:	26 Gallons / 100 Liter
Fluid Types:	Motor Oils, Transmission Fluids, Hydraulic Oil, Power Steering Fluids, Engine Coolant
Min. Bowl Height:	51.25"
Max. Bowl Height:	78.5"
Weight:	74 lbs. (29.5 kg)



Large Tool Tray



Oil Filter Drain



Fixed Regulator and Pressure Relief Valve



Oversized Wheels

