

Introducing Lincoln's New Family of Power Cord and Light Reels



*Designed for Light-, Medium-
and Heavy-Duty Applications
in Home, Vehicle Maintenance
and Factory Environments.*



Model 91025



Model 91028



Model 91026



Model 91034



Model 91032

**1 YEAR
WARRANTY**

LIGHT DUTY



Model 91024



Model 91025

Cord Type/Length:	SJTOW / 30 ft.	SJTOW / 30 ft.
Cord Thickness:	18 AWG	16 AWG
No. of Conductors:	2	3
Pigtail:	4 ft. with 2-prong plug	4 ft. with 3-prong plug
Voltage/Current:	125 VAC / NA	125 VAC / 10A
End Accessory:	13W fluorescent light	Triple tap

HEAVY DUTY



Model 91030



Model 91031

Cord Type/Length:	SJTOW / 50 ft.	SJEOW / 45 ft.
Cord Thickness:	16 AWG	12 AWG
No. of Conductors:	3	3
Pigtail:	4 ft. with 3-prong plug	4 ft. with 3-prong plug
Voltage/Current:	125 VAC / 13A	125 VAC / 20A
End Accessory:	Single receptacle	Single receptacle

SJTOW – Hard service cord for general use at 300 volts, rated at -31°F to +140°F, PVC thermoplastic insulated and jacketed, oil resistant and rated for outdoor use.

MEDIUM DUTY



Model 91026



Model 91027



Model 91028



Model 91029

SJTOW / 50 ft.	SJTOW / 50 ft.	SJTOW / 50 ft.	SJTOW / 50 ft.
18 AWG	18 AWG	18 AWG	14 AWG
2	2	2	3
4 ft. with 2-prong plug	4 ft. with 2-prong plug	4 ft. with 2-prong plug	4 ft. with 3-prong plug
125 VAC / NA	125 VAC / NA	125 VAC / NA	125 VAC / 12A
13W fluorescent light	30 LED light	60 LED light	Triple tap

HEAVY DUTY



Model 91032



Model 91033



Model 91034

SJEOW / 45 ft.	SJTOW / 50 ft.	SJTOW / 50 ft.
12 AWG	16 AWG	16 AWG
3	2	3
4 ft. with 3-prong plug	4 ft. with 3-prong plug	4 ft. with 3-prong plug
125 VAC / 20A	125 VAC / 0.3A	125 VAC / 10A
Duplex outlet box with GFCI (F)	Fluorescent light	Fluorescent light and outlet

SJEOW – Hard service cord for general use at 300 volts, rated at -58°F to +221°F, TPE thermoplastic elastomer insulated and jacketed, oil resistant and rated for outdoor use.

**1 YEAR
WARRANTY**

Light-Duty Reel Features

- 30 ft. SJTOW cold weather compatible cord – grease, oil and water resistant
- Available with fluorescent light or trip tap extensions
- Steel housing
- Adjustable cord stop with anti-kink cord spring
- Wall or ceiling mounting
- Perfect for home, small service shops and tire/muffler/fast lube shops



Medium-Duty Reel Features

- 50 ft. SJTOW cold weather compatible cord – grease, oil and water resistant
- Available with LED, fluorescent light or trip tap extensions
- Heavy-duty flame-resistant ABS housing
- Adjustable cord stop with anti-kink cord spring
- Wall, ceiling or bench mount with three fixed-angle position steel mounting bracket
- Perfect for vehicle maintenance and industrial environments



Heavy-Duty Reel Features

- Cord is cold weather compatible – grease, oil and water resistant
- Available with fluorescent light, with and without power tap, single outlets, dual GFCI outlets
- Spring retractable with latch
- Engineered for heavy-duty, industrial use
- Adjustable cord stop
- Wall, ceiling or bench mount
- Perfect for vehicle maintenance and industrial environments



LINCOLN
An SKF Group Brand

Form No. 444561 (3/11)
© Copyright 2011

America:
St. Louis, MO 63120
1-314-679-4200
FAX: 1-800-424-5359
www.lincolnindustrial.com

Europe/Near East/Africa/India:
Walldorf, Germany
49-6227-33-0
FAX: 49-6227-33-259
www.lincolnindustrial.de

Asia/Pacific:
Singapore
(65) 6588-0188
FAX: (65) 6588-3438
sales@lincolnindustrial.com.sg

An SKF Group Brand

SKF