

# 1:1 ratio fluid transfer pump

Provides quick and efficient fluid transfer



Model 384829

The Lincoln 1:1 ratio fluid transfer pump was designed for quick, reliable and economical transfer of motor oil, ATF, gear oil and hydraulic fluids from all types of standard containers. An upgraded version of Lincoln's proven pump technology, it provides a practical method of delivering fluid from large storage tanks or drums, through supply lines, to hose reels or other bulk oil service outlets. In addition, these high-volume pumps are suitable for use with 16 and 55 gallon (60,5 and 208 liter) drums and bulk storage tanks. Each pump comes with a 33 1/2 in. (85 cm) plastic extension tube that can be cut to fit the specific tank or drum depth.

Operating under constant pressure, this positive-displacement pump starts automatically when the dispense valve is opened and shuts off automatically when the valve is closed. It features a universal suction tube and is capable of use with installed piping, hose and spigot valves, as well as suitable for installation on mobile lube carts.

## 1:1 ratio fluid transfer pump advantages:

- Efficiently and quickly transfers fluids from all types of standard containers
- Delivers proven, reliable performance at a competitive price
- Pump stalls against pressure and is activated by opening dispense valve
- Features universal suction tube
- Functions in harsh environments
- Capable of use with installed piping, hose and spigot valves and can be installed on mobile lube carts
- Totally serviceable

# Upgraded version of proven Lincoln pump technology



**Model 384829**  
Shown with 55 gallon (208 liter) drum, hose and control valve (sold separately)

## Technical data

1:1 ratio pump stalls against pressure permitting pump to be turned on/off with the control valve

Maximum input/output pressure	200 psi (13,8 bar)
Air inlet	1/4 in. NPTF (f)
Fluid outlet	1 in. NPTF (f)
Free delivery	14 gal./min. (53 l/min.)

Displacement per cycle	10 1/2 in. <sup>3</sup> (172 cm <sup>3</sup> )
Bung bushing	integrated, 2 in.
Universal suction tube	33 1/2 in. (85 cm), can cut to fit specific tank or drum depth

Stub pump material	metal
--------------------	-------

Optional	low-level cut-off valve
----------	-------------------------

## Recommended pipe and tubing lengths

Delivery line data for four quarts (*one liter*) of oil or more per minute at 40 °F (4 °C) with 150 psi (10,34 bar) at the pump

	5/8 OD x 0.035 in. (1,6 OD x 0,09 cm) wall steel tube or 1/2 in. (1,3 cm) pipe	7/8 OD x 0.035 in. (2,2 OD x 0,09 cm) wall steel tube or 3/4 in. (1,9 cm) pipe
--	---	---

10 or 5W/20	75 ft. (22,86 m)	200 ft. (60,96 m)
20 or 10W/30	20 ft. (6,09 m)	50 ft. (15,24 m)

## Hose and control valve examples

Order no.	Description
-----------	-------------

High flow (shown in photo)

<b>282930</b>	3/4 in. (19 mm) control valve
<b>1230120</b>	3/4 x 10 ft. (19 x 3 048 mm) lubricant hose
<b>67302</b>	3/4 NPT (f) x 1 in. NPT (m) adapter

Standard

<b>758F</b>	1/2 in. (12,7 mm) control valve
<b>73120</b>	1/2 in. x 10 ft. (12,7 x 3 048 mm) lubricant hose
<b>274285</b>	1/2 NPT (f) x 1 in. NPT (m) adapter

See lubrication equipment catalog for other control valve, dispense meter and lubricant hose options.

Please contact:

**SKF USA, Inc.**

5148 N. Hanley Road  
St. Louis, MO 63134 USA  
Tel. +1 (314) 679-4200

[skf.com](http://skf.com) | [lincolnindustrial.com](http://lincolnindustrial.com)

© SKF is a registered trademark of the SKF Group.

© Lincoln is a registered trademark of Lincoln Industrial Corp.

© SKF Group 2016

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

PUB LS/P2 16546 EN · May 2016