

# 75 ft. (23 m) dual support hose reel

## Exceptional stability for rugged, demanding applications

- The 75 ft. (23 m) dual support hose reel is designed based on the proven 94000DS series reels with the added feature of greater hose length
- The heavy-duty reel includes a dual arm and dual pedestal that gives the needed foundation for demanding environments
- Dual support from base to axle to roller outlet provides stability for applications with heavy vibration and impact
- Easy to install
- Assembled reels come with 75 ft. (23 m) delivery hose, ball stop and 2 in. (5,08 cm) inlet hose
- For use in high ceiling, fleet and municipalities, mining workshops and applications requiring shared reel banks
- Made in the U.S.A. and comes with a special 5 year warranty



### 75 ft. (23 m) dual support hose reel specifications

Model no.	Description	Hose	Application	Working pressure	Inlet/outlet
<b>94200DS</b>	Bare reel	75 ft. (23 m) capacity	Air and water	1 000 psi (69 bar)	1/2 in. NPTF
<b>94400DS</b>	Bare reel	75 ft. (23 m) capacity	Oil	4 000 psi (276 bar)	1/2 in. NPTF
<b>94600DS</b>	Bare reel	75 ft. (23 m) capacity	Grease	8 000 psi (552 bar)	3/8 in. NPTF
<b>94273DS</b>	Assembled	3/8 in. x 75 ft. (23 m)	Air and water	300 psi (207 bar)	1/2 in. NPTF
<b>94274DS</b>	Assembled	1/2 in. x 75 ft. (23 m)	Air and water	300 psi (207 bar)	1/2 in. NPTF
<b>94474DS</b>	Assembled	1/2 in. x 75 ft. (23 m)	Oil	2 000 psi (138 bar)	1/2 in. NPTF
<b>94673DS</b>	Assembled	3/8 in. x 75 ft. (23 m)	Grease	4 000 psi (276 bar)	3/8 in. NPTF

# 50 ft. (15 m) dual support hose reel

The 50 ft. (15 m) dual support reel utilizes the same technology as Lincoln's dependable 94000 reels. These heavy-duty reels include a dual arm, dual axle and dual base to give the added stability needed for demanding environments.

The three-point bolt design on the support arm allows for easy hosing of the reel at installation and provides instant access to the reel's working parts.



## Features

- Design based on the proven 94000 series reels
- Dual support from base to axle to roller outlet provides stability for applications with heavy vibration and impact
- Easy to install
- Made in the U.S.A. and comes with a special 5 year warranty

## 50 ft. (15 m) dual support hose reel specifications

Model no.	Description	Hose	Application	Working pressure	Inlet/outlet
<b>94100DS</b>	Bare reel	50 ft. (15 m) capacity	Air and water	1 000 psi (69 bar)	1/2 in. NPTF
<b>94300DS</b>	Bare reel	50 ft. (15 m) capacity	Oil	4 000 psi (276 bar)	1/2 in. NPTF
<b>94500DS</b>	Bare reel	50 ft. (15 m) capacity	Grease	8 000 psi (552 bar)	3/8 in. NPTF
<b>94163DS</b>	Assembled	3/8 in. x 50 ft. (15 m)	Air and water	300 psi (20,7 bar)	1/2 in. NPTF
<b>94154DS</b>	Assembled	1/2 in. x 50 ft. (15 m)	Air and water	300 psi (20,7 bar)	1/2 in. NPTF
<b>94354DS</b>	Assembled	1/2 in. x 50 ft. (15 m)	Oil	2 000 psi (138 bar)	1/2 in. NPTF
<b>94553DS</b>	Assembled	3/8 in. x 50 ft. (15 m)	Grease	4 000 psi (276 bar)	3/8 in. NPTF

© SKF is a registered trademark of the SKF Group.

© Lincoln is a registered trademark of Lincoln Industrial Corp

© SKF Group 2011

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

SKF PUB LS/P2 12337 EN · November 2011 · FORM 444569

