

LINCOLN

®

LINCOLN'S NEW GREASE PUMP, HOIST AND FOLLOWER KIT

Lincoln's positive priming follower prevents pump cavitation and eliminates trapped air in the drum.

The flexible follower wipes the drum's side clean and leaves little or no grease at the bottom of the drum.

The easy one-hand air valve operation of Lincoln's Grease Pump Hoist effortlessly lifts the pump high enough for easy, clean removal and replacement of grease drums.



***PNEUMATIC OPERATION MAKES
PUMP INSERTION/EXTRACTION SAFE AND EASY!***

Features & Benefits

- The weight of the pump which is attached to the follower plate reduces cavitation, air pockets and helps keep the pump primed
- Flexible, tight-fitting follower wipes drum sides clean—reducing wasted grease
- Pneumatic operation makes pump insertion/extraction easy
- Easy, one-hand air valve operation increases productivity and reduces risk of injury
- Air regulator provides just enough pressure to smoothly and safely extract and insert the pump
- Durable and reliable construction is a perfect fit for heavy-duty shop environment
- 7' air and grease hoses connect quickly to supply lines



Model 2710

With PowerMaster® III (50:1) pump for 400 lb. drum

Model 2740

With Series 40 (50:1) pump for 400 lb. drum

With Lincoln's
PowerMaster® III
and Series 40 pumps

Product Specifications

	Model 2710	Model 2740
Pump Model	2010 (50:1) Includes 84804 air motor, 84995 pump tube	84668 (50:1)
Max. Working Pressure	4000 psi	5000 psi
Max. Air Pressure	80 psi	100 psi
Air Inlet	1/2 NPTF male x 84" hose (1/2 " ID hose)	1/4 NPTF male x 84" hose (1/4 " ID hose)
Lube Outlet	1/2 NPTF female x 84" hose (3/8" SAE 100R2)	1/4 NPTF male x 84" hose (1/4" SAE 100R2)
Elevator Pressure	40 - 100 psi	40 - 100 psi
Raised Height	103"	97"