

Models 3665, 3667 and 3669 low-profile truck drains

A professional alternative to lifting heavy vehicles during fluid changes

Lincoln models 3665, 3667 and 3669 truck drains offer a low-profile design that can be easily positioned under high-clearance vehicles for capturing used fluids including motor oil, coolant and transmission fluid. All three models feature a 17 gallon (65 liter) capacity reservoir molded from robust, lightweight high-impact polypropylene and mounted on four 4 in. (100 mm) diameter swivel casters. Overall height is only 7 3/4 in. (195 mm). The top of the reservoir features a large 20 x 29 in. (510 x 735 mm) recessed area for capturing fluid and a removable metal screen which covers the reservoir opening to keep out debris. Recessed pockets at each corner provide storage for drain plugs and filters.

Lincoln truck drains offer a choice of three discharge methods:

- **Model 3665**
Features a 6 ft. (1,8 m) long discharge hose with a 3/4 in. camlock style connector and cap. The hose extends from the bottom of the reservoir and can be connected to a diaphragm pump or other fluid transfer system to evacuate fluid from the reservoir.



Model 3669

Model 3667

Features a rotary hand pump mounted horizontally to the front of the reservoir and a 6 ft. (1,8 m) long discharge hose with a steel J-hook installed at the outlet. Fluid is discharged from the reservoir by manually operating the pump.

- **Model 3669**

Features a durable 120 V electric pump installed below the front of the reservoir. The pump operates when plugged into a standard power outlet and discharges fluid through a 6 ft. (1,8 m) hose with steel J-hook.

Pump specifications

Manual pump output
1 gal. (3,8 liter)/15 revolutions

Electric pump output
1 gal. (3,8 liter)/minute (10W-30 at room temperature)

2.6 gal. (9,8 liter)/minute (antifreeze)

Models 3665, 3667 and 3669 low-profile truck drains

Model 3665



* Model 3665 connects to any of the three Lincoln diaphragm pump kits (models 4100, 4102 or 4104).

Model 4100

For use with model 3665



Lincoln offers three models of diaphragm pump evacuation kits for evacuating used fluid drains using a 3/4 in. camlock style connector, such as model 3665. The kits include a diaphragm pump and all recommended air supply, fluid extraction, and fluid discharge fittings, components and accessories.

Diaphragm pump evacuation kits


Model 4100 features 1 in. (25,4 mm) UL-approved aluminum double-diaphragm pump model 85634, recommended for transferring flammable liquids.

Model 4102 features 1 in. (25,4 mm) non-UL aluminum double-diaphragm pump (model 85627), recommended for transferring non-flammable liquids.

Model 4104 features 1/2 in. (12,7 mm) non-UL aluminum double-diaphragm pump (model 85631), for transferring non-flammable liquids.



Model 3667



Model 3669

Please contact:

SKF USA, Inc.

One Lincoln Way

St. Louis, MO 63120 USA

Tel. +1 (314) 679-4200

© SKF is a registered trademark of the SKF Group.

© Lincoln is a registered trademark of Lincoln Industrial Corp.

© SKF Group 2013

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

SKF PUB LS/P2 13939 EN · July 2013 · FORM 444583

