

# Mini workbench reel

Lincoln's smallest reel excels in the tightest places

- Compact size allows for easy installation under workbenches or in cabinets
- Narrow 5.25 in. (13,34 cm) width and 14 in. (35,56 cm) spool makes this the most narrow reel in its class
- 1 in. (2,54 cm) quality spring provides reliable, consistent performance and retractability
- 5-year warranty
- Integrated swivel stem and shaft design means easy servicing by simply removing the swivel body
- High gloss, UV-resistant powder coat finish reduces scuffs and impact marks



### Mini workbench reel specifications

Model	Pressure	Fluid	Dimensions		Length	
			Diameter			
			in.	mm	ft.	m
81133	Low	Air/water	3/8	9,5	35	10,67
81323	Medium	Oil	3/8	9,5	25	7,62

# Lincoln's new line of oil bar and spigots

Modular three spigot capable steel oil bar in a compact new design. Two different spigot variations are available to choose from that have a locking or non-locking handle. The locking version is ideal when used with a LFC5000. The oil bar has punch outs to add a digital 812 meter if the user wants to see the quantity being dispensed. A flow control valve is also offered to control the flow and pressure at the spigot.



## Available models

Model	Description
84951	3 spigot capable steel oil bar (does not include spigots)
277564	Locking spring-loaded oil spigot
277565	Non-locking spring-loaded oil spigot
277566	15 gallon/minute brass flow control valve
812	Universal digital inline meter measuring in quarts, gallons or liters.

© SKF is a registered trademark of the SKF Group.

© Lincoln is a registered trademark of Lincoln Industrial Corp

© SKF Group 2011

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

SKF PUB LS/P2 12339 EN · November 2011 · FORM 444570

