

**MODEL NO.:** 980

**DESCRIPTION:** Electronic Lube Meter

**PRODUCT AND PACKAGING SPECIFICATIONS:**

Maximum Flow:	8 GPM / 30 LPM
Minimum Flow:	0.25 GPM / 1 LPM
Operating Pressure (Maximum):	1500 PSI / 10,350kPa / 103.5 Bar
Operating Temperature:	-4° F (-20° C) to 140° F (60° C)
Fluids Applicable:	Motor Oils (SAE 5 through 30), Gear Oils (SAE 80 through 240), Automatic Transmission Fluid, Engine Coolant, Windshield Wiper Fluid Solution
Fluid Contacted Material:	Aluminum, Acetal, Nitrile (NBR), Mild Steel
Accuracy:	+/- 0.5%
Display Unit(s):	Pints, Quarts, Gallons, or Liters
Inlet & Outlet Connections:	½" FNPT
Weight:	3.7lbs. (1.7kg)
Unit Carton Qty:	1 ea.
Unit Carton Size:	7-3/4"H x 5-1/2"W x 26"L
Pkg Languages:	English
UPC Code:	095992100999
SCC Code:	10095992100996
Harmonization Code:	9026.10.2040
Service Parts Available:	Yes
CE Approved:	Yes



**APPLICATION:**

- Standard /Heavy duty applications: Vehicle maintenance, lube trucks, industrial environment.

**KEY FEATURES:**

- Large six digit LCD display with two decimal point precision
- Unit of measure selectable from the front of register
- Totalization in gallons or liters
- Resettable and non-resettable totalizer
- Low battery indicator
- Long life, field replaceable, top load battery
- 90° flex hose with swivel and manual tip
- 1/2" ball bearing swivel
- Built-in trigger guard
- Locking trigger

**INCLUDES:**

- Control valve, meter, flexible 90° extension, manual tip and instruction manual